



Power Unit Comparison Chart

	Flo-Master M80	AirMaster A700T2	AirMaster A900r2Q	Flo-Master F700T2	SilentMaster S900
Motor	Single 1-stage 5.7 inch thru-flow	Single 2-stage 5.7" thru-flow	Dual 3-stage 5.7" by-pass motors Motor	Single 2-stage 5.7" thru-flow	Dual 3-stage 5.7" by-pass motors
Max Air Watts	461	700	866	700	905
Max Amps	2.8	7.6	7.6	7.6	13
Waterlift	111.7 inch	145.9	136.0	145.9 inch	139 inch
CFM @ 2" opening	120.5	133	190	133	191
Voltage	240	240	240	240	240
Height	20 inch	39.5 inch	39.5 inch	37 inch	37 inch
Weight	15 lb	29 lb	45 lb	38 lb	49 lb
Trash Capacity	5 gallon	5 gallon	8 gallon	8 gallon	8 gallon
Microfiltration	Closed Bag	Microtex Inverted Cloth & Tru-Seal Closed Bag	Tru-Seal® Closed Bag System Filtration	Tru-Seal Closed Bag System	Tru-Seal® Closed Bag System Filtration
Suggested Max Footage	3,000 ft2	10,000 ft2	20,000 ft2	10,000 ft2	20,000 ft2
Quietness	62 dB _A	62 dB _A	64 dB _A	65 dB _A	64 dB _A
pdf Info Sheet	N/A	Available	Available	Available	Available
Motor	Single 1-stage 5.7 inch thru-flow	Single 2-stage 5.7" thru-flow	Dual 3-stage 5.7" by-pass motors Motor	Single 2-stage 5.7" thru-flow	Dual 3-stage 5.7" by-pass motors
Max Air Watts	461	700	866	700	905
Max Amps	2.8	7.6	7.6	7.6	13

All models 240V 50/60HZ